

# 2002 GUIDELINES FOR COST EFFECTIVE ENERGY MANAGEMENT IMPROVEMENT PROJECTS

For use with Building Energy Management Programs Financing beginning July 1, 2001

# **Department of Natural Resources**

Energy Bureau Wallace State Office Building 502 E. 9th Street Des Moines, Iowa 50319-0034 (515) 281-5145 Fax (515) 281-6794

## **TABLE OF CONTENTS**

Introduction	3
Cost Effective	3
Aggregate Implementation Package	4
Final BEM Financing Package	4
List of EMI Savings and Costs form	5
Energy Management Plan form	6
EMI Codes and Useful Lives	7

This material was prepared with the support of the U.S. Department of Energy (DOE). However, any opinions, findings, conclusions or recommendations expressed herein are those of the authors and do not necessarily reflect the views of the DOE.

#### INTRODUCTION

The goal of the Iowa Building Energy Management (BEM) Programs is to reduce energy costs for taxpayer supported facilities. The Programs provide access to the financing needed to identify and implement technically viable, cost-effective Energy Management Improvements (EMI). The Programs have established agreements with private sector legal and financial resources that make the necessary funds available to BEM clients including schools, local governments, hospitals, private colleges and state facilities.

Previously, Iowa law and policy directed that analyses be comprehensive and that the package of EMIs proposed for Program financing have an aggregate six-year payback. However, Iowa Code Section 473.20, subsection 1, has recently been amended (with strike through of original text shown) to read as follows:

1. The department may make loans to the state, state agencies, political subdivisions of the state, school districts, area education agencies, community colleges, and nonprofit organizations for implementation of energy conservation measures identified in a comprehensive engineering analysis. Loans shall not be made for energy conservation measures that require more than an average of six years for the state, state agency, political subdivision of the state, school district, area education agency, community college, or nonprofit organization as an entity to recoup the actual or projected cost of construction and acquisition of the improvements; and cost of the engineering plans and specifications be made for all cost effective energy management improvements. For the state, state agencies, political subdivisions of the state, school districts, area education agencies, community colleges, and nonprofit organizations to receive a loan from the fund, the department shall require completion of an energy management plan including an energy audit and a comprehensive engineering analysis. The department shall approve loans made under this section.

Therefore, effective July 1, 2001 BEM Programs will be able to provide financing for all cost-effective energy projects in public facilities (not just those within the aggregate six-year payback). It is the goal of this guideline document to define cost effective in a way that is accurate, simple to derive, easily understood, and minimizes administrative costs.

## **COST EFFECTIVE**

Cost effective is defined as the ability to recoup the actual or projected cost of construction and acquisition of the improvement, and cost of the engineering plans and specifications within the useful life of the improvement, or incremental cost of the lowest life cycle cost design alternative.

The means of determining which projects are cost effective for approval of BEM financing as explained below.

#### AGGREGATE IMPLEMENTATION PACKAGE

An aggregate payback package of EMIs is the total installation costs (including design, etc.) of all EMIs to be installed divided by the total of the annual savings. This enables short payback projects to be combined with longer payback projects that may not otherwise be implemented. This is one of the benefits of the comprehensive BEM program offering.

### FINAL BEM FINANCING PACKAGE

Prior to the completion of the Technical Engineering Analysis (TEA) or Energy Audit (EA) report, the analyst or auditor is required to put EMI projects in a logical order of implementation priority so that the final report savings totals account for EMI interaction. (Refer to the current Technical Engineering Analysis Guidelines or Energy Audit Guidelines). From the final report, the analyst is able to determine, with input from the client, the complete package of projects to recommend for financing. The maximum available term for BEM financing is 12 years. Clients will be required to implement, at a minimum, all improvements that fall within a 3 year simple payback period.

Refer to the current version of the Department's Technical Engineering Analysis Guidelines or Energy Audit Guidelines for further discussion of BEM requirements for the financing package, as well as technical and documentation requirements of the BEM programs.

The *List of EMI Savings and Costs* form (copied from the TEA Guidelines) is provided below as a sample of some of the documentation requirements of the BEM programs. EMIs are to be listed on the form in order of recommended implementation. Additional documentation is required for incremental financing based on life cycle cost.

In addition, the following *Energy Management Plan* (copied from the TEA and EA Guidelines) is required for each study or studies conducted under the TEA or EA contract. The analyst works with the client to develop the *Energy Management Plan* (EMP) during the facility analysis, however, the EMP often encompasses the results of several reports (such as when the analysis contract covers several buildings). The EMP is the document representing the end product of the analysis contract and serves as a plan of action for the client. If necessary, the analyst is to provide narrative text explaining the contents of the EMP and summarize the contents of the EMP form. For each EMI, this form records the analyst's implementation recommendation, implementation order, and implementation schedule. This information is recorded on the EMP and is submitted with the report(s) to the Department.

2002 Cost Effective Guidelines Page 5

List of EMI Savi	ngs and Costs
Institution	Building

Remaining useful life of building \_\_\_\_ years

EMI	Page	Project Title	Electricity Savings		Demand Savings		Natural Gas Savings		Non-Energy Savings
#			kWh/yr	\$/yr	kW	\$/yr	CCF/yr	\$/yr	\$/yr

EMI #	EMI Type	EMI Material Cost	EMI Labor Cost	EMI Design Cost	Manage- ment Fee *	Initial Capital Outlay	EMI Rebate	Net EMI Cost	Savings (\$/yr)	Simple Payback (years)	Aggregate SPB (years)	EMI Useful Life

<sup>•</sup> Management fee includes energy services company (ESCO) or performance contract overhead and profit charges, and/or construction management costs, as applicable.

Energy Ma	anagement Plan	
Institution	Number (if any)	Page of

Building #	EMI #	EMI Code	EMI Title	Electricity Savings (kWh)	Natural Gas Savings (Therms)	Annual Cost Savings (\$/yr)	EMI Cost	Simple Payback (years)	Aggre- gate SPB (years)	EMI Useful Life (years)	Rec. Y or N	Implemen- tation Date	Method of Financing
	1		Totals										

# **EMI Codes and Useful Lives**

Useful Life in Yrs.

in Yrs.							
Building Envelope							
	Insulation						
25	BRR	Roof/Ceiling insulation					
25	BRW	Wall insulation					
25	BRC	Combination roof/ceiling and wall insulation					
25	BRO	Other insulation measures					
	Infiltration Control						
10	BIZ	Infiltration control					
	Fenestration/Windows						
25	BFS	Storm windows					
25	BFD	Double glazing					
25	BFT	Triple glazing					
25	BFI	Replace glass with insulated panels					
15	BFF	Reflective film					
25	BFW	Wall up or close off					
15	BFX	Other window measures					
	Other Openings (e.g. doors, loading docks, etc.)						
25	BOS	Storm doors					
25	BOA	Air locks or vestibules					
25	BOW	Wall up or close off openings					
25	BOX	Other door/miscellaneous measures					
		Renewable					
	Solar						
10	RSW	Solar hot water					
10	RSA	Active solar space conditioning					
20	RSP	Passive solar space conditioning					
10	RSV	Photovoltaic application					
	Wind, Hydro						
20	RBZ	Use of wind energy					
10	RGZ	Use of water power					
	Renewable Conversions						
25	RCB	Conversion to biomass					
20	RCG	Geothermal heat pump					
25	RCM	Conversion to methane					
25	RCR	Conversion to refuse					
25	RCW	Conversion to wood					
25	RCX	Conversion to other renewable					

.

Useful Life in Yrs.

in Yrs.							
Mechanical Systems							
	Non-Renewable Conversions						
25	MCC	Conversion to coal					
25	MCE	Conversion to electricity					
25	MCG	Conversion to natural gas					
25	MCO	Conversion to oil					
25	MCX	Conversion to another non-renewable fuel					
	Controls						
10	MKC	Central control/automated energy management					
10	MKE	Enthalpy control					
10	MKS	Shut down/shut off devices					
10	MKT	Temperature reset devices					
10	MKX	Other control devices					
	Air-Conditioning						
25	MAC	Chiller conversion/efficiency improvement					
15	MAE	Install economizer					
25	MAU	Package unit application					
15	MAX	Other air-conditioning measure					
	Domestic Water						
10	MWC	Reduce circulation pump operation					
15	MWD	Decentralized hot water heater					
20	MWF	Install flow restrictors					
20	MWI	Insulate tanks					
15	MWX	Other water measure					
	Other						
10	MOE	Install energy recovery devices					
20	MOG	Cogeneration application					
	Heating Modifications						
10	MHA	Install automatic ignition device					
25	MHB	Replace burner					
25	MHD	Downsize system					
15	MHE	Install stack economizer					
10	MHF	Install automatic flue damper					
10	MHH	Install humidification device					
25	MHO	Replace boiler					
20	MHP	Preheat combustion air/make up water					
15	MHT	Install turbulators					
10	MHX	Other heating modification					

Useful
Life
in Yrs.

in Yrs.							
Mechanical Systems (continued)							
Air Distribution System Modifications							
15	MDA	Reduce air volume					
20	MDI	Insulate pipes or ductwork					
10	MDO	Install automatic dampers					
15	MDS	Prevent air stratification					
15	MDT	Repair/replace steam traps					
15	MDV	Install variable air volume system					
20	MDR	HVAC retrofit or replacement					
10	MDX	Other distribution system modification					
10	MDZ	Zoning modifications					
	Swimming Pools						
10	MPC	Install swimming pool cover					
15	MPD	Pool dehumidification					
15	MPR	Pool heat recovery					
Electrical/Lighting							
	Lighting Conversions						
20	ECE	Convert to T8s and electronic ballasts					
20	ECF	Convert to fluorescent lights					
20	ECH	Convert to high intensity discharge (HID) lamps					
25	ECL	Convert exit light fixtures to LED exit fixtures					
10	ECW	Install reduced wattage fluorescent lamps					
8	ECX	Convert to other high efficiency lamps					
	Lighting Modifications						
20	EMB	Install energy efficient ballasts					
20	EMD	Disconnect ballasts					
8	EMF	Modify fixture (e.g. reflectors, lower height, etc.)					
20	EMR	Reduce number of fixtures/task lighting					
10	EMZ	Other lighting modification					
	Controls						
10	EKD	Install demand limiter controls					
10	EKZ	Electrical system control devices					
	Motors						
20	MME	Install energy efficient motors					
20	MMS	Down size motors					
20	MMV	Install VFDs					
20	MMX	Other motor modification					
	Other Electrical						
10	EEZ	Other electrical applications					